

Slings & Tiedowns

Webmaster® 1600 Polyester Web Slings



- The industrial standard in web slings
- Red core warning yarns aid inspection process
- Polyester web stretches less, for better load control
- Tuff-Tag for permanent identification, required by OSHA
- Yellow abrasion resistant treatment
- Wrapped bearing point for longer sling life

Part #	Width (In.)	Length (Ft.)	Rated Capacities (Lbs.)		
			Vertical	Choker	Basket
EE2801DWTX4	2	4	6400	5000	12800
EE2802DWTX6	2	6	6400	5000	12800
EE2802DWTX8	2	8	6400	5000	12800
EE2802DWTX10	2	10	6400	5000	12800
EE2802DWTX12	2	12	6400	5000	12800
EE2802DWTX20	2	20	6400	5000	12800
EE4802DWX6	2	6	10000	8000	20000
EE4802DWX10	2	10	10000	8000	20000
EE4802DWX12	2	12	10000	8000	20000
EE4802DWX16	2	16	10000	8000	20000
EE4802DWX20	2	20	10000	8000	20000

Tuflex® Roundslings



- Double wall cover for greater sling life
- Color-coded capacities for quick identification
- No strength loss from abrasion to cover
- Wear points can be shifted to extend sling life
- Easier to inspect than any other type of sling
- Chokes tighter, releases easier than other slings

Part #	Color	Length (Ft.)	Rated Capacities (Lbs.)		
			Vertical	Choker	Basket
EN60X4	Green	4	5300	4200	10600
EN60X6	Green	6	5300	4200	10600
EN60X10	Green	10	5300	4200	10600
EN90X6	Yellow	6	8400	6700	16800
EN90X8	Yellow	8	8400	6700	16800
EN90X10	Yellow	10	8400	6700	16800
EN90X12	Yellow	12	8400	6700	16800
EN90X16	Yellow	16	8400	6700	16800
EN90X20	Yellow	20	8400	6700	16800

Adjust-A-Link™ Adjustable Chain Slings

- The most versatile style of chain sling
- Adjust one or multiple links at one time to keep load level
- Complies with OSHA – proof tested and certified
- Grade 100 chain – alloy steel master link



Single Leg Rating – 2700 Lbs. Part # 30001G10
 Double @ 60° - 4700 Lbs. 7/32" x 6 ft.

LoadHugger® Tiedowns



- Meets all DOT and CVSA requirements
- Flexible, conforms to and controls the load
- Ratchet assembly allows fast, easy adjustment

Part #	Fitting	Width	Length	Ult. Strength	WLL
61001	Flat Hook	2"	27 ft.	10,000 Lb.	3,300 Lb.
26422	U-Hook	2"	27 ft.	10,000 Lb.	3,300 Lb.
26424	Flat Hook	4"	27 ft.	15,000 Lb.	5,000 Lb.

Connective Systems & Supply

555 W 48th Avenue, Unit B, Denver, CO 80216 • 970-310-7385
 5718 Wright Drive, Loveland, CO 80538-8840 • 970-663-0304