

The fasteners are designed for use in
Ramset T3SS Single-Shot Gas Tool



SELECTION CHART

THREADED ROD HANGER

For suspended ceilings, piping and other items using 1/4" or 3/8" threaded rod. Fastener is pre-assembled to a 16 gage threaded rod hanger. 100 per jar.




PART NUMBER	DESCRIPTION
14TRHMP034	1/4" Rod hanger with 3/4" plated pin
38TRHMP034	3/8" Rod hanger with 3/4" plated pin

Shank diameter = .104/.125 Head diameter = .300

ONE HOLE STRAP

Used to attach EMT conduit or armored cable to concrete. Fastener pre-assembled to a 16 gage conduit strap. 100 per jar, 3/8" 200 per jar.



PART NUMBER	DESCRIPTION
38HSMP034*	3/8" Hole strap with 3/4" plated pin 
12HSMP034	1/2" Hole strap with 3/4" plated pin
34HSMP034	3/4" Hole strap with 3/4" plated pin
10HSMP034	1" Hole strap with 3/4" plated pin

Shank diameter = .104/.125 Head diameter = .300 *38HSMP034 = 18 gage, 200 per jar

CONDUIT CLAMP

Used to attach conduit to concrete. Pin pre-assembled to an 18 gage conduit strap. 1/2" 50 per jar and 3/4" 25 per jar.



PART NUMBER	DESCRIPTION
12CCMP034L	1/2" Conduit clamp with 3/4" plated pin
34CCMP034L	3/4" Conduit clamp with 3/4" plated pin

Shank diameter = .104/.125 Head diameter = .300

CEILING CLIP ASSEMBLY

Pre-assembled Ceiling Clip. Plated 14 gage clip. 100 per jar.



PART NUMBER	DESCRIPTION
34CLIP	3/4" wide angle clip w/ 3/4" length pin

Shank diameter = .104/.125 Head diameter = .300

AVAILABLE IN CONVENIENT JARS!



The new durable plastic containers mean less waste on the jobsite, or in the back of a truck. Their wide-mouth design makes it easy to grab what you need.



Each T3SS gas accessory and pin label provides vital holding value information—taking away the guess work.

The fasteners are designed for use in
Ramset T3SS Single-Shot Gas Tool



SELECTION CHART

TIE STRAP HOLDER

Used to install temporary lighting and secure low voltage cable to concrete, uses a standard cable tie up to 3/8" in width. Fastener is pre-assembled to a 22 gage tie strap holder. 50 per jar.




PART NUMBER	DESCRIPTION
TSHMP034	Tie strap holder with 3/4" plated pin

Shank diameter = .104/.125 Head diameter = .300

MECHANICAL PIN WITH WASHER

Used for the attachment of light gage metal to concrete and steel such as HVAC duct strap to concrete. Plated pin pre-assembled to a 1/2" domed washer. 200 per jar, 1" 100 per jar.



PART NUMBER	DESCRIPTION
M012	1/2" Plated step pin with dome washer
M034	3/4" Plated pin with domed washer
M034BB	3/4" Premium step pin with domed washer
M100	1" Plated pin with domed washer

Shank diameter = .125, Step Pin .104/.118 Head diameter = .300 (M012 = .250)
 *Will fit R150 & T3SS with optional work contact element, P/N: M150200

MUST USE WITH MAGNETIC WORK CONTACT ELEMENT (M150200)

1/4-20 THREADED STUD

Used to attach electrical components to concrete where removability of the component is required. Plated threaded stud. 200 per jar.



PART NUMBER	DESCRIPTION	SHANK LENGTH
14STUD	1/2"	5/8"

Shank diameter = .125

NOT MADE IN USA

TOP HAT PIN

Used for general purpose fastening to concrete.
 Plated pin with top hat. 200 per jar.



PART NUMBER	DESCRIPTION
MPO34TH	3/4" Plated pin with top hat

Shank diameter = .125 Head diameter = .300

BRIDLE RING

Pre-Assembled 2" Bridle Ring supports low voltage, data com, signal, and control cables
 50 per box.



PART NUMBER	DESCRIPTION
BR2	2" Bridal ring

Shank diameter = .125